



RVS SERIES

The REEFE® premium vortex sump pump is specifically designed for the most demanding jobs with industrial grade motor insulation (Class F) and cast iron impellers. Every pump is factory tested for quality assurance and is ultra-reliable. High quality guaranteed.



- Waste water applications
- Waste water treatment systems
- Sullage pumping, storm water
- Pool & tank emptying

FEATURES & BENEFITS

- Cast iron vortex impeller for durability
- Thermal overload protection
- High performance
- 10m power cable H07RN-F
- Includes hosetail
- Max liquid temperature 40°C

CONSTRUCTION

- Stainless steel motor housing & shaft
- Cast iron vortex impeller
- Dual mechanical seal in oil chamber
- Motor insulation Class F
- Cast iron base and outlet
- Depth adjustable MAC 3 float switch on auto models
- Extremely reliable construction

:		
	RVS90	DA .
	RVS72	
	RVS12	
	RVS85	
E :		
Head (m)		
Ë		
	,	
	o 100 200 300 400 500 600 700 800 900 100 Flow (Litres/Minute)	0 1100 1200
	Tiow (Littles) Fillitate)	

	MODEL	OPERATION	POWER		RATED		MAXIMUM		SOFT	ᄣᆂ	OUTLET		=	SIZE	
CODE			VOLTS	AMPS	KW	FLOW (L/MIN)	HEAD (M)	FLOW (L/MIN)	HEAD (M)	SOLIDS HANDLING	CABLE	MM BSP	INCH BSP	WEIGHT (KG)	LXWXH (MM)
13793	RVS900A	Auto	240	9.8	1.5	600	5.0	900	8.5	65mm	10m	80	3	38	497 x 221 x 607
13809	RVS900M-3	Manual	415	3.4	1.5	600	5.0	900	8.5	65mm	10m	80	3	38	497 x 221 x 607
13816	RVS1200M-3	Manual	415	4.7	2.2	600	8.5	1200	12	65mm	10m	80	3	39	544 x 242 x 647
19184	RVS720A	Auto	240	9.2	1.5	400	12	720	18	50mm	10m	80	3	30	497 x 221 x 607
19214	RVS720M-3	Manual	415	3.1	1.5	400	12	720	18	50mm	10m	80	3	38	497 x 221 x 607
19191	RVS850M-3	Manual	415	4.3	2.2	400	16	850	20	50mm	10m	80	3	39	544 x 242 x 647