DUAL HOT WATER CIRCULATOR PUMP SETS

The Reefe[®] Deluxe Hot/Cold water circulator pump sets can be used in a range of applications including domestic and commercial buildings to save water and time, and cooling and heating of machinery and other processes. Circulator pumps, consisting of a control panel and pumps mounted on a vertical steel frame, are designed to circulate water from a storage tank through a ring-main system and back to the storage tank for re-heating.

APPLICATIONS

- Commercial and domestic hot water circulating
- Laundries and hospitals
- Laboratories
- Hydroponics
- Hotels, motels and aged care facilities
- High rise buildings
- Hot water and cold water circulating

FEATURES & BENEFITS

- Pumps constructed from non corrosive material
- Pre-plumbed and pre-wired ready for installation
- 24-hour/ 7-day time clock
- Thermostat input
- Easy to use dual pump controller
- Inter-connectable with BMS

CONSTRUCTION

- Heavy duty galvanised wall bracket
- 25mm stainless steel manifolds
- 25mm valves and unions
- IP65 controller





40cm

| | Refer to page 100 for further information on the Deluxe Dual Hot Water Pump Controller |
|--|---|
|--|---|

| CODE | PUMP MODEL | CONTROL PANEL | DESCRIPTION |
|-------|------------|---------------|--|
| 12925 | RHC2060 | Deluxe | REEFE® Dual hot water circulating pump system. Comprising of two (2) 240 volt RHC2060 pumps, deluxe alternating pump controller and stainless steel pump manifolds with valves and fittings mounted on galvanised steel wall brackets. |
| 18699 | RHC3280 | Deluxe | REEFE® Dual hot water circulating pump system. Comprising of two (2) 240 volt RHC3280 pumps, deluxe alternating pump controller and stainless steel pump manifolds with valves and fittings mounted on galvanised steel wall brackets. |