ELECTION START AVAILABLE IN SOME MODELS



REEFE





RP TWIN IMPELLER SERIES

These Premium grade Honda powered pumps are engineered with quality materials to produce a proven reliable pump. Boasting exceptionally heavy duty construction, these pumps are guaranteed to deliver well in tough environments.



80 70 60 50 40 30 20 10 0 100 200 50 150 300 400 0 Flow (Litres/Minute)

APPLICATIONS

- · Fire-fighting
- Boom spraying
- Wash-down applications
- Water transfer

FEATURES & BENEFITS

- Genuine GP160 HONDA engine backed by Honda 1 year universal warranty
- Genuine GX200 HONDA engine backed by Honda 3 year universal warranty
- Self-priming to 6 metres with foot valve
- Engine with oil sensor
- Available with or without roll frame
- 2 year warranty on wet end and roll frame
- Wiring harness available as an option for battery connection
- Suitable for pumping clean fresh water only

CONSTRUCTION

- Alloy twin impeller and diffuser
- Hose tails, hose clips and suction strainer included
- Heavy duty cast inlets and outlets
- 3/4" threaded shaft

CODE	MODEL	ENGINE	FUEL TANK	SUCTION SIZE	DISCHARGE SIZE	MAX HEAD (M)	MAX FLOW RATE (L/MIN)	PUMP BODY	HORSE POWER CLASS	WEIGHT (KG)
17821	GP015TR	Honda GP160, Recoil Start	3.1L	1.5"	1x1.5"/2x1"	76	350	Alloy	5.5	27
17838	GP015TR-RF	Honda GP160, Recoil Start w Roll Frame	3.1L	1.5"	1x1.5"/2x1"	76	350	Alloy	5.5	31
8645	RP015TR	Honda GX200, Recoil Start	3.1L	1.5"	1x1.5"/2x1"	76	350	Alloy	6.5	27
6740	RP015TR-RF	Honda GX200, Recoil Start w Roll Frame	3.1L	1.5"	1x1.5"/2x1"	76	350	Alloy	6.5	31
8683	RP015TE	Honda GX200E, Electric Start	3.1L	1.5"	1x1.5"/2x1"	76	350	Alloy	6.5	27
6788	RP015TE-RF	Honda GX200E, Electric Start w Roll Frame	3.1L	1.5"	1x1.5"/2x1"	76	350	Alloy	6.5	31