

POND & WATER FEATURE PUMPS 240V

RP SERIES

CODE	PUMP MODEL	CABLE LENGTH	DRY MOUNT FLOODED	INLET	OUTLET	WATTS	MAX Litres/Hr	MAX HD (m)	DIMENSIONS			RRP
									L (mm)	W (mm)	H (mm)	
9017	RP260	5m	NO		10mm push fit	5.5	260	0.45	60	45	60	33.15
9031	RP550	5m	NO		10-13mm push fit	10	550	1.22	75	50	70	45.65
9062	RP610	10m	YES	½" BSP	¾" BSP	11	610	1.2	120	60	85	62.15
9192	RP900	10m	YES	½" BSP	½" BSP	19	900	1.9	120	60	85	84.15
9093	RP1100	10m	YES	½" BSP	½" BSP	17	1100	2.0	130	90	105	95.15
9123	RP1500	10m	YES	½" BSP	½" BSP	20	1500	2.0	130	90	110	114.50
9154	RP2400	10m	YES	1" BSP	½" BSP	40	2300	2.4	155	100	120	154.40
9178	RP3500	10m	YES	1" BSP	¾" BSP	60	3500	2.4	170	120	150	169.70
9185	RP4000	10m	YES	1" BSP	¾" BSP	70	4000	2.75	170	120	150	186.50



ABOUT

Economical, quiet running, centrifugal pumps with generous cable lengths. These pumps have numerous applications for aquarium, garden fountains, table and wall fountains and hydroponics.

APPLICATIONS

- Water Features
- Garden Ponds
- Indoor Fountains
- Urns and Amphoras
- Table Fountains
- Hydroponics
- Statues

FEATURES

- Proven Performance
- Fresh or Salt Water
- Fully Submersible
- Quiet, Continuous Operation
- Built in Flow Control
- Spare Parts Available

Head	Approximate Flow Rate in Litres per Hour (Without Restriction)								
2.75m									(0@2.75m)
2.50m							(0@2.4m)	(0@2.4m)	400
2.25m							300	300	1000
2.00m					(0@ 2.0m)	(0@ 2.0m)	600	600	1300
1.75m				(0@1.9m)	200	250	850	1000	1650
1.50m				200	400	500	1150	1500	2000
1.25m		(0@ 1.2m)	(0@ 1.2m)	300	650	700	1350	2000	2400
1.00m		40	100	475	700	850	1600	2500	2700
0.75m		170	220	550	825	1000	1750	3000	3000
0.50m	(0@0.45m)	400	450	675	950	1200	2000	3150	3400
0.25m	150	480	525	800	1075	1350	2200	3300	3600
0.00m	260	550	610	850	1100	1500	2300	3500	4000
MODEL	RP260	RP550	RP610	RP900	RP1100	RP1500	RP2400	RP3500	RP4000