

POND & WATER FEATURE PUMPS

LOW VOLTAGE RPLV SERIES

CODE	PUMP MODEL	CABLE LENGTH	DRY MOUNT FLOODED	DIMENSIONS			INLET	OUTLET	WATTS	MAX L/HR	MAX HD (M)	RRP
				Length (mm)	Width (mm)	Height (mm)						
9604	RP550LV 12 volt	5m	NO	75	50	70		10-13mm push fit	10	550	1.22	63.45
9659	RP850LV 24 volt	10m	YES	120	90	85	½" BSP	½" BSP	19	850	1.8	128.76
9673	RP1100LV 24 volt	10m	YES	130	90	105	½" BSP	½" BSP	17	1100	2.0	148.85
9697	RP1500LV 24 volt	10m	YES	130	90	110	½" BSP	½" BSP	20	1500	2.0	167.65
9727	RP2400LV 24 volt	10m	YES	155	100	120	1" BSP	½" BSP	40	2300	2.4	220.00
9758	RP4000LV 24 volt	10m	YES	170	120	150	1" BSP	¾" BSP	70	4000	2.75	281.65
9901	Low Voltage Extension Lead	10m	-	-	-	-	-	-	12V- 24V	-	-	54.15

ABOUT

Economical quiet running, centrifugal pumps in safelow voltage, with generous 10m cable lengths on the RP850LV upwards and outdoor transformers. These pumps have numerous applications for aquariums, garden fountains, table and wall fountains and hydroponics. All are saltwater compatible and are fitted with flow control and pre-filter foam on RP850LV upwards.

APPLICATIONS

- Water Features
- Garden Ponds
- Indoor Fountains
- Urns And Amphora's
- Table Fountains
- Hydroponics
- Statues

FEATURES

- Proven Performance
- Fresh Or Salt Water
- Fully Submersible
- Quiet, Continuous Operation
- Built In Flow Control
- Low Voltage Outdoor Transformer



Outdoor Transformer included. 10m cable on RP850LV - RP4000LV

Head (M)	Approximate Flow Rate in Litres per Hour (Without Restriction)						
2.75							(0 @ 2.75m)
2.50						(0 @ 2.4m)	400
2.25						300	1000
2.00				(0 @ 2.0m)	(0 @ 2.0m)	600	1300
1.75			(0@1.8m)	200	250	850	1650
1.50			200	400	500	1150	2000
1.25		(0 @ 1.2m)	300	650	700	1350	2400
1.00		40	475	700	850	1600	2700
0.75		170	550	825	1000	1750	3000
0.50	(0 @ 0.45m)	400	675	950	1200	2000	3400
0.25	150	480	800	1075	1350	2200	3600
0.00	260	550	850	1100	1500	2300	4000
MODEL	RP260	RP550	RP850	RP1100	RP1500	RP2400	RP4000