



NO	Name	Spec.	Material	Quantity
1	Cable	3 × 0.75mm ²		1
2	Cable seal pad		NBR	1
3	Screw	M6 × 20	SUS201	2
4	Handle		PA6+GF20	1
5	Protected ring		NBR	1
6	Upper cover		PA6+GF20	1
7	O-Ring	D150 × 3.1	NBR	1
8	Nut		H62	1
9	Cable holder		NBR	1
10	Pad		H62	1
11	Screw	M6 × 10	SUS201	6
12	Pad for oil hole		NBR	2
13	Screw	M6 × 175	SUS201	4
14	Spring pad	φ 6		8
15	Internal cover		ADC12	1
16	Wiring dcagram		Sticker	1
17	O-Ring	D110 × 3.1	NBR	1
18	Capacitor	20uF/450V	NBR	2
19	Connection terminal	φ 5		3
20	Screw	M6 × 16	SUS201	4
21	Protected sleeve		NBR	1
22	Screw	M5 × 8	Plating zinc	1
23	Pad	φ 5	NBR	1
24	Pad	φ 5		1
25	Back cover		ADC12	1
26	Wave spring pad	D35		1
27	Bearing	6202-2RS		2
28	Rotor with shaft			1
29	Stator			1
30	Shalf spring pad	d17		1
31	Shalf spring pad	d14		2
32	Sleeve		6063A	1
33	Motor housing		70#	1
34	Front flange		ADC12	1
35	Sleeve		SUS304	1
36	Name plate		Sticker	1
37	O-ring	D130 × 3.1	NBR	1
38	Mechanical seal			2
39	Outlet section		ADC12	1
40	O-ring	D65 × 3.1	NBR	1
41	Mechanical seal greaser		PA6+GF20	1
42	Mechanical seal lubricating		N7#	1
43	Pad	φ52 × φ 1# 2	STU304	1
44	Last diffusor		PP0+GF20	1
45	Impeller		PP0	3
46	Hydraulic stack		PP0	2
47	Pad	φ 10	SUS201	1
48	Spring pad	φ 10	SUS201	1
49	Nut	M 10×1	SUS201	1
50	Cover plate		PA6+GF20	1
51	Base		PA6+GF20	1
52	Pad	φ 6	SUS201	8
53	Screw	M6 × 90	SUS201	8