



POND & WATER FEATURE PUMP LOW VOLTAGE

RPLV SERIES

Economical quiet running, centrifugal pumps in safe, low voltage, with generous 10m cable lengths (except RP550LV) and outdoor transformers. These pumps have numerous applications for aquariums, garden fountains, table and wall fountains and hydroponics. All are saltwater compatible and are fitted with flow control and prefilter foam (except RP550LV)

APPLICATIONS

- Water features
- Garden ponds
- Indoor fountains
- Urns and amphoras
- Table fountains
- Hydroponics
- Statues

FEATURES & BENEFITS

- Reliable performance
- Fresh or salt water
- Fully submersible
- Quiet, continuous operation
- Built in flow control
- Low voltage outdoor transformer with 10m cable (except RP550LV - 5m cable)
- Transformers have Electrical Safety Approval



TRANSFORMER



RP550LV

Head (m)	Approximate Flow Rate in Litres per Hour (without restriction)					
2.75						(0@2.75m)
2.5					(0@2.4m)	400
2.25					300	1000
2.0				(0@2.0m)	(0@2.0m)	600 1300
1.75			(0@1.8m)	200	250	850 1650
1.5			200	400	500	1150 2000
1.25		(0@1.2m)	300	650	700	1350 2400
1.0		40	475	700	850	1600 2700
0.75		170	550	825	1000	1750 3000
0.5	(0@0.45m)	400	675	950	1200	2000 3400
0.25	150	480	800	1075	1350	2200 3600
0.0	260	550	850	1100	1500	2300 4000



RP850LV-RP4000LV

MODEL	RP260LV	RP550LV	RP850LV	RP1100LV	RP1500LV	RP2400LV	RP4000LV
-------	---------	---------	---------	----------	----------	----------	----------

CODE	MODEL	POWER		MAXIMUM		DRY MOUNT FLOODED	CABLE LENGTH (M)	INLET (MM)	OUTLET (MM)	SIZE L X W X H (MM)
		WATTS	VOLTS	FLOW (L/HR)	HEAD (M)					
9604	RP550LV	10	12	550	1.22	NO	5		10-13mm push fit	75x50x70
9659	RP850LV	19	24	850	1.8	YES	10	½" BSP	½" BSP	120x90x85
9673	RP1100LV	17	24	1100	2.0	YES	10	½" BSP	½" BSP	130x90x105
9697	RP1500LV	20	24	1500	2.0	YES	10	½" BSP	½" BSP	130x90x110
9727	RP2400LV	40	24	2300	2.4	YES	10	1" BSP	½" BSP	155x100x120
9758	RP4000LV	70	24	4000	2.75	YES	10	1" BSP	¾" BSP	170x120x150
9901	Low Voltage 10m Extension Lead 12V- 24V									