

RSWE40 SHALLOW WELL JET PUMP

WITH PRESSURE CONTROLLER

EU SERIES







The REEFE® self-priming jet pump has been specifically constructed for high demands of suction lift. Suitable for the supply of water to house and garden, stock watering troughs and wash down applications. 100% European made, guaranteeing quality and longer service life.

APPLICATIONS

- Clean water transfer
- Surface mounted shallow wells
- Household supply not recommended for drinking water
- Garden sprinklers and irrigation
- Stock watering
- Spear pumping

FEATURES & BENEFITS

- Suction lift up to 9m
- Easy to mount and install
- Corrosion resistance coating to all wet end internals
- Available in multiple combinations:
 - Pump Only
 - -with Automatic pressure controller (PC)
 - with Pressure tank, switch & gauge

CONSTRUCTION

- Anti-corrosive cast iron pump body
- Aluminium motor bracket
- Techno-polymer diffuser, nozzle, venturi and impeller
- Stainless steel 304 pump shaft
- Carbon-ceramics mechanical seals
- Class F Insulation
- IP44 Motor Protection
- IP54 Terminal Board Protection



22139.PTS

22139.PC



Œ	40	П	Т	П		Т	П		Ī	Ī	T	ī				Ī							Т	Т	
Head (m)	35						Н		_	H	H	H	=	7							-		H		
Ĭ	30	Н	1		4				4	4	\dashv	\dashv	4	4		_					\exists	4	+		
	25	H	+	\vdash		1				+	ł	-		-	_								+		
	20	Н	+			+	₽			1	7	۲	4								-		+	+	
	15	Н	+	H	Н	ł	H		4	+	\dashv	4	-								-	4	+	H	
	10	Н	H			H	₽		\dashv	\dashv	\dashv	\dashv	-								\exists	\dashv	+	+	
		Н	+		Н		H		4	4	4	4									٠.,	4	4	H	
																						٠.,	.		
		0			10			20	0				30					0		5(L i		es/	min	ute	50

AVAILABLE AS PUMP ONLY OR WITH PRESSURE TANK, SWITCH & GAUGE

	•	
CODE	MODEL	SIZE
22139	RSWE40	380x180x195
22139.PTS	RSWE40	380x180x635

C		MODEL	POWE	R 240V	RATED		MAXIMUM		SUCTION	NO. OF	OUT	LET	WEIGHT	SIZE	
	CODE		AMPS	WATTS	FLOW (L/MIN)	HEAD (M)	FLOW (L/MIN)	HEAD (M)	LIFT (M)	TAPS	ММ	INCHES	(KG)	LXWXH (MM)	
	22139.PC	RSWE40	2.6	600	25	21	50	35	9	4-6	25	1	10	380x180x395	