

FLOAT SWITCH 10A

FS SERIES

The REEFE® series of float switches are suitable for water pumps and professional plumbing systems automation. Guarantee reliable integration with your pump and control equipment.

APPLICATIONS

- Pump out and tank fill control
- Suitable for use in sewage and stormwater stations
- High level alarm switch
- Run dry protection for low level sensing
- Tank Level Control

FEATURES & BENEFITS

- Neoprene Cables for resistance to chemicals and oils
- Includes easily adjustable counter weight
- Can be configured for close on rise and close on fall operation
- Unique switch design where there is no contact with ball and switch preventing shorts due to corrosion
- 3m Float supplied without counterweight



CODE	MODEL	CABLE LENGTH	FUNCTION
22702	FS03	3m Cable	Double
20630	FS05	5m Cable	Double
20647	FS10	10m Cable	Double
20654	FS20	20m Cable	Double
20661	FS30	30m Cable	Double

FEATURE	SPECIFICATIONS
Cable	(FS) H07 RN-F3X1 - Ø7.5MM(2 func.) (FS1) H07 RN-F 3G1 - Ø8.8MM (1 func.)
Casing	Polypropylene
Counterweight Shell	230g (Refer image 1)
Power Supply	Max. 10 (8) A, 240V
Activation Angle	45° Degrees
Depth	Max 10m
Temperature	Max 45C°
Protection Grade	IP68

COUNTERWEIGHT

Image 1

