



## VARIABLE SPEED DRIVE

VSC SERIES

The REEFE variable speed drives feature superior pressure sensing technology to maintain constant pressure and motor speed during pump operation, with the added advantage of power savings. Easy to operate and mount on pump. Water flows through hydraulic connections.

### APPLICATIONS

- Intelligent, automatic, constant pressure operation of pressure pumps for a multitude of situations, domestic, commercial & industrial
- Mains Pressure Boosting
- Hotels, Amenities, Restaurants

### FEATURES & BENEFITS

- Power savings through intelligent control
- Automatic operation eliminating the need for manual resets/operation
- Integrated protection system to prevent dry-running operation
- Compact design and easy to install
- Supplied with Quick Plug connections and 1.5m power cable
- VSC1-12 can be interconnected for Duty Cycle dual pump applications
- Ingress Protection IP55
- Max liquid temperature 40°C
- Max ambient temperature 50°C
- Certified to AS/NZS4020 for use with potable water



CODE	MODEL	INPUT VOLTAGE	kW	OUTPUT VOLTAGE	MAX AMPS	RANGE OF SET PRESSURE	MAX FLOW (L/MIN)	INLET   OUTLET		WEIGHT (KG)
								MM	IN	
21897	VSC1-7.5	1- / 240V	1.5	1- / 240V	7.5	0.5-8bar	133	25	1"	2.8
21903	VSC1-12	1- / 240V	2.5	1- / 240V	12		167	32	1 ¼"	