

EXTERNAL RAIN MAINS SYSTEM

RM4000-3



The RainPro RM4000-3 system is designed for speed of installation - The Rain Mains device has no cables, no float, no solenoid, no electronic controls. The simplicity of this system has the added benefit of making it very affordable. The RM4000-3 restricts flow of mains supply while rain water is being pumped to help conserve water. This system is suited for applications supplying laundry and toilets, and is also suitable for cabins or small houses with one bathroom.

APPLICATIONS

- Domestic toilet & laundry
- Small house / cabin / granny flat (1 bathroom)
- Small commercial / industrial*
- Garden irrigation*
- Toilet blocks (up to 6 fixtures)*
- Construction / mine site offices*


*Check specifications required

FEATURES & BENEFITS

- Rains to Mains switch over system allows mains water to flow if tank water is unavailable, and restricts mains flow if tank water is sufficient
- Mains flow up to 50L/Min
- Valveset is 100% hydraulic - no electronics
- Reliable, efficient power-saving performance
- Automatic pressure controller giving consistent pressure supply, automatically checks for water every 24 hours after a run dry event
- Run dry protection and thermal overload protection for the pump
- Certified to AS/NZS4020 for potable water
- WaterMark certified, includes dual check valve on mains
- WaterMark # 022109

CONSTRUCTION

- Stainless-steel casing and shaft
- Carbon/ceramic mechanical seal for durability
- Quick plug pressure controller connection
- Ingress Protection IP54
- Insulation Class F



CODE	DESCRIPTION	POWER 240V			MAXIMUM		SIZE L X W X H (MM)
		AMPS	P1 (kW)	P2 (kW)	FLOW (L/MIN)	HEAD (M)	
22740	RM4000-3 with PRJ55 Pump with RMV3550 Valve	2.5	0.65	0.37	60	34	340x190x460
21309	RM4000-3 with PRJ65 Pump with RMV3550 Valve	4.0	0.85	0.6	78	43	380x210x490
21316	RM4000-3 with PRJ80 Pump with RMV3550 Valve	5.5	1.1	0.75	80	48	400x210x500