



VARIABLE SPEED MULTISTAGE PUMP

VSRE SERIES

The REEFE VSRE series are designed with advanced technologies for super-efficient flow of clean water in various applications. Available in an extensive range of sizes, these market leading pumps are built to meet varying demands and requirements. European quality, VSRE pumps feature a highly durable construction to guarantee extended service life. Assembled with a variable speed drive, the pump can respond to demands in application, guaranteeing perfect pressure.

APPLICATIONS


- Whole house supply
- Amenities blocks, hotels, restaurants
- Irrigation Supply
- Mains Pressure Boosting
- Stock Watering Systems

FEATURES & BENEFITS

- Highly efficient, energy saving design
- Heavy duty, durable construction for extended service life
- Externally ventilated motor for superior heat control
- Automatic restart after loss of prime event
- Certified to AS/NZS4020 for use with potable water
- Max Water Temperature 35°C

CONSTRUCTION

- Stainless Steel AISI304 pump body and impeller
- Stainless Steel AISI416 shaft
- Carbon-graphite mechanical seal
- Noryl/fibreglass impellers & diffusers
- Thermal overload protection
- 1.5m power cable
- Quick plug connection
- Supplied with 2L Pressure Tank
- Ingress Protection IP44
- Insulation Class F



CODE	MODEL	POWER 240V			SUPPLIED VSD DRIVE	RATED		MAXIMUM		NO. OF TAPS	INLET OUTLET		WEIGHT (KG)	SIZE L X W X H (MM)
		AMPS	P1 (kW)	P2 (kW)		FLOW (L/MIN)	HEAD (M)	FLOW (L/MIN)	HEAD (M)		MM	IN		
21620	VSRE40-60	3.5	0.79	0.6	VSC1-7.5	30	35	60	40	2-4	25	1"	9.75	357x260x500
21637	VSRE38-110	4.2	0.83	0.75	VSC1-7.5	55	27	110	38	4-6	25	1"	13.05	353x260x519
21644	VSRE52-110	5.4	1.24	0.8	VSC1-7.5	55	37	110	52	5-8	25	1"	13.55	372x260x519
21651	VSRE67-120	7.2	1.66	1.2	VSC1-7.5	60	47	120	67	6-10	25	1"	14.25	392x260x519
24966	VSRE78-120	7.8	1.79	1.2	VSC1-12	60	58	120	78	6-10	25	1"	14.95	410x260x519
25000	VSRE92-120	8.6	1.98	1.5	VSC1-12	60	68	120	92	6-10	25	1"	16.35	430x260x519

SEE OVER (PAGE 18) FOR ADDITIONAL SIZES