



WASTEWATER PUMP PIT

QGWP MINI SERIES

Light duty polyethylene collection pits are ideal for confined spaces and restricted spaces. Common uses would be for temporary applications, where wastewater needs to be removed. These systems are recommended to be installed in domestic and residential applications only.

APPLICATIONS


- Pumping wastewater
- Building sites and other temporary applications
- Screened wastewater removal

FEATURES & BENEFITS

- Compact design for easy installation
- Preassembled - ready to install
- Thermal overload protection
- Can handle up to 40°C
- Up to 30mm solids handling (Refer to pump model details on specific sizing)
- Not suitable for raw sewage

CONSTRUCTION

- 300 Pit = 40L
- 450 Pit = 85L
- 600 Pit = 180L
- Class A Poly Lid - Pedestrian
- Inlet to be installed on site
- 1 ½" | 40mm MBSP inlet/outlet excluding RVS155VF Pump Pits. RVS155VF: 1 ¼" | 32mm MBSP supplied with 32-40mm poly bush
- Assembled with submersible pumps



MINI 3 SERIES with SOLID LID - 300sq WASTEWATER PIT

CODE	MODEL	PUMP MODEL	OUTLET SIZE	SIZE L X W X H (MM)	CAPACITY
23020	QGWP160-300	RVS155VF	1 ¼" 32mm	360 x 360 x 450	40L
23051	QGWP230-300	RVS250VF	1 ½" 40mm	360 x 360 x 450	40L



MINI 4 SERIES with SOLID LID - 450sq WASTEWATER PIT

CODE	MODEL	PUMP MODEL	OUTLET SIZE	SIZE L X W X H (MM)	CAPACITY
23037	QGWP160-450	RVS155VF	1 ¼" 32mm	560 x 560 x 505	85L
23068	QGWP230-450	RVS250VF	1 ½" 40mm	560 x 560 x 505	85L
23129	QGWP300-450	RVS300VF	1 ½" 40mm	560 x 560 x 505	85L
23099	QGWP260-450	RVC260	1 ½" 40mm	560 x 560 x 505	85L
23143	QGWP320-450	RVC315	1 ½" 40mm	560 x 560 x 505	85L



MINI 6 SERIES with SOLID LID - 600sq WASTEWATER PIT

CODE	MODEL	PUMP MODEL	OUTLET SIZE	SIZE L X W X H (MM)	CAPACITY
23044	QGWP160-600	RVS155VF	1 ¼" 32mm	715 x 715 x 660	180L
23075	QGWP230-600	RVS250VF	1 ½" 40mm	715 x 715 x 660	180L
23136	QGWP300-600	RVS300VF	1 ½" 40mm	715 x 715 x 660	180L
23105	QGWP260-600	RVC260	1 ½" 40mm	715 x 715 x 660	180L
23150	QGWP320-600	RVC315	1 ½" 40mm	715 x 715 x 660	180L

