

POLY PUMP WELLS

Polyethylene pump wells are strong, lightweight and UV resistant rotomoulded tanks. All tanks are engineered to Australian standard AS 1546, approved by NSW Health, and covered by a 5 year warranty.

<p>2000L POLY PUMP WELL 190 KG</p>	<p>3000L POLY PUMP WELL 245 KG</p>	<p>5000L POLY PUMP WELL 370 KG</p>	<p>DOWNLOAD OPERATIONS MANUAL</p>
<p>Code: 25864 Access Opening: 600x600</p>	<p>Code: 25338 Access Opening: 600x900</p>	<p>Code: 13205 Access Opening: 600x900</p>	
  <p>Technical drawing details for 2000L: Side view shows a height of 2040mm, a top diameter of 1200mm, and a base diameter of 1100mm. Top view shows a square access opening of 738mm x 738mm. Rib thickness is 13mm. Base rib is R10 all around.</p>	  <p>Technical drawing details for 3000L: Side view shows a height of 2167.10mm, a top diameter of 1650mm, and a base diameter of 1750mm. Top view shows a square access opening of 1040mm x 1040mm. Rib thickness is 18mm. Base rib is R15 all around.</p>	  <p>Technical drawing details for 5000L: Side view shows a height of 2500mm, a top diameter of 1925mm, and a base diameter of 1825mm. Top view shows a square access opening of 1040mm x 1040mm. Rib thickness is 18mm. Base rib is R15 all around.</p>	<p>QUOTE REQUEST FORM</p> 

NOTE: The Pump Wells and the Access Covers are sold separately. Please advise which type of Access Cover is required.