



POLY PUMP 2" 3"

MH POLY SERIES

These premium grade Honda powered pumps are fitted with a poly wet end, noryl impeller and viton seals to suit pumping of agricultural chemicals and some other mildly corrosive liquids. Always check suitability of the liquid with seal types before proceeding. Engine covered by a 3 year manufacturer's warranty, 2 year warranty on the wet end.

APPLICATIONS

- Salt water
- Wastewater
- Liquid fertilisers ¹
- Milk ²
- Some milk acids

FEATURES & BENEFITS

- Genuine HONDA engine - backed by Honda 3 year universal warranty
- Corrosion resistant wet end
- 2 year warranty on wet-end
- Rubber mounts
- Engine with oil sensor


CONSTRUCTION

- Noryl impeller and volute
- Viton mechanical seal, EPDM check valve & o-rings
- Carry handle

ENGINE DRIVEN

SUCTION LIFT INFO - 2" POLY	
Suction Head (m)	Max Flow (L/Min)
0	725
-1.5	707
-3	686
-4.5	660
-6	575

SUCTION LIFT INFO - 3" POLY	
Suction Head (m)	Max Flow (L/Min)
0	735.13
-1.5	735.06
-3	734.98
-4.5	698.11
-6	369.86



NOTE

1. Check suitability with seal types before proceeding.
2. Not food grade.
3. Not suitable for molasses or molasses mixture.

CODE	PUMP MODEL	ENGINE HONDA	START	CARRY HANDLE	FUEL TANK	SUCTION SIZE	DISCHARGE SIZE	MAX HEAD (M)	MAX FLOW RATE (L/MIN)	PUMP BODY	HORSE POWER CLASS	WEIGHT (KG)
20050	RP020P	GX200	Recoil	Yes	3.1L	2"	2"	44	650	Poly	5.5	26
20067	RP030P	GX200	Recoil	Yes	3.1L	3"	3"	35	800	Poly	5.5	27