

LIQUID LEVEL ALARM FLUSH INDOOR

Housed behind an attractive standard switch plate, is the unique flush mounting Liquid Level Alarm. Purpose built for the modern home environment, where septic, wastewater and rain water tanks, both above ground and below ground, have become a common feature. This discreet device blends with the decor of any home. The level alarm can be used for either low or high level alerts and provides for a safe, low voltage cabling installation between tank float switch and display unit.

FEATURES & BENEFITS

- Discreet flush mounted plate
- · Ideal for septic, wastewater
- Suitable for below or above ground tanks
- Safe low voltage cabling
- Supplied with 10m float switch





CODE	MODEL
12989	Standard Liquid Level Alarm with float switch - for indoor

DOL STARTER 1 PHASE & 3 PHASE

The DOL Starter, housed in a robust, powder coated, lockable metal enclosure, provides a very cost effective way of controlling a pump where the usual standard features, typically available in pump controllers, are not required. Available for 240V and 415V applications.

FEATURES & BENEFITS

- Auto / manual / off switching
- Low voltage (24VAC) circuitry for input switches
- Contactor and overload motor protection for pumps
- In addition to a low voltage switch input the starter also has provision for a 'cut out' switch
- · Amps to be specified



COD	E	MODEL	DESCRIPTION		
945	1	RPC15900	Direct On-Line 1 Phase 240V Starter		
2699	91	RPC15905	Direct On-Line 3 Phase 415V Starter		

DUAL HOT WATER CONTROLLER

The dual hot water pump controller are available in a range of 2 configurations. The Deluxe control panel has all of the standard functions of the REEFE RPC Dual Pump controller with the addition of the time clock and has a dedicated provision for thermostat input for circulator pumps with thermostatic control. The Economy control panel is a simple controller in a poly enclosure for 2 pumps with timer for 4 hour pump alternation and an additional timer for system control in auto mode. No provision for temperature thermostat.

FEATURES & BENEFITS

- 24 hour / 7 day timer
- Deluxe Controller:
 - · Highly durable and functional electronic keypad for ease of use
 - Circuit breaker protected low voltage control and input circuitry for safety
 - Lockable mains isolator for safety
 - Auto / manual / off operation of both pumps
 - Thermal overload protection of pump motors
 - Visual and audible alarms complete with mute switch
 - LED indicator lights for system status indication
 - IP44 weatherproof, lockable powder coated metal enclosures
 - · Inter-connectable with BMS





DELUXE

CODE	MODEL	VOLTAGE	AMPS	ENCLOSURE	AUDIO / VISUAL ALARM	THERMOSTAT INPUT
27011	Economy	240	Max 6A	Poly	No	No
27028	Deluxe	240	Max 18A	Metal	Yes	Yes