

DUAL HOT WATER CONTROLLER

The dual hot water pump controller are available in a range of 3 configurations for every application. The Deluxe control panels has all of the standard functions of the REEFE Dual Pump controller with the addition of the time clock. The Deluxe model has dedicated provision for thermostat input for circulator pumps with thermostatic control, while the Kompakt model can be fitted with a thermostat by wiring it in series with the time clock.

FEATURES & BENEFITS

- Highly durable and functional electronic keypad for ease of use on Deluxe model
- 24 hour / 7 day timer on all models
- Circuit breaker protected low voltage control and input circuitry for safety on Deluxe and Kompakt models
- Lockable mains isolator for safety on Deluxe model
- Auto / manual / off operation of both pumps on Deluxe model
- Thermal overload protection of pump motors on Deluxe model
- Visual and audible alarms complete with mute switch on Deluxe model
- LED indicator lights for system status indication on Deluxe model
- IP44 weatherproof, lockable powder coated metal enclosures complete with removable gland plate on Deluxe model
- External door option available so control keypad is protected from the weather / tampering on Deluxe model
- Inter-connectable with BMS on Deluxe model
- The Economy model cannot be used with a Thermostat
- The Economy model does not have a visual or audible alarm



DELUXE



ECONOMY

CODE	DESCRIPTION	VOLTAGE	AMPS	ENCLOSURE	AUDIO/VISUAL ALARM	THERMOSTAT INPUT
27011	Economy Dual HWC Controller with Time Clock	240	Max 6A	Poly	No	No
27028	Deluxe Dual HWC Controller with Time Clock	240	Max 18A	Metal	Yes	Yes